# ELECTRIC CHAIN HOIST - TWIN HOOK

**CAPACITY RANGE FROM UP TO 3.2 TONS** 



#### **EFFORTLESS AND BALANCED LIFTING**

Twin hook electric chain hoists are equipped with two hooks with a single operating motor and gear box.

Most suitable for lifting applications requiring two lifting points for a wide load or retaining a level lifting and in a synchronous way.

Twin hook chain hoists are simple, reliable and smooth running.

#### SPROCKET

Two chains are winded up to the same sprocket.

Over travel limit is controlled by geared limit switch as standard.

#### HOOK CENTER

Each Hoist is built with a specific hook centers that best fits the given application.

#### **OPTIMAL SPACE UTILIZATION**

Compact dimensions and best hook approach.



### **STANDARD SPECIFICATIONS**

**CAPACITY RANGE** 2 x 500 kg to 2 x 1600 kg

**DUTY CYCLE** Dual Speed – 40/20 % ED

**RATINGS** Hoist – IP55 Pendant – IP65

**LIFT HEIGHT** 3-12m (Longer lifts available)

**STANDARD VOLTAGE** 3 Phase, 380 – 415 V, 50Hz **CLASSIFICATION** ISO M5 FEM 2M

**Chain** BS-EN-818-7

**CT SPEED** 25/6 m/min

**Control Voltage** 48V **OVERLOAD PROTECTION** Slipping Clutch

**CHAIN FALLS** Single chain fall Double chain fall

**OPERATING CONDITIONS** -10° to + 50° C

**STANDARD PENDANTS** Single speed: 2-button Dual speed: 2-button (With two steps) With emergency On/Off



## PRODUCT RANGE

MODEL	CAPACITY (KG)	LIFTING SPEED (m/mm)	FALL	CLASS OF DUTY	MOTOR POWER (KW)	CHAIN SIZE	HOOK CENTER DISTANCE (MM)
CA 2010T	2x500	8/2	1	2m/M5	1.5/0.37	7x21	1000-4000
	2x1000	4/1	2				
CA 3216T	2x800	8/2	1		2.4/0.6	9x27	
	2x1600	4/1	2				





We also offer ANNUAL MAINTENANCE CONTRACT for all cranes, exclusively for our Customers.

For Service queries : service@carlstahlcraftsman.com

1800-121-12121

CARL STAHL CRAFTSMAN ENTERPRISES PRIVATE LIMITED.

Registered Office, No. 1078, Senthel Towers, 4th Floor Avanashi Road Coimbatore - 641 018 Tamilnadu, India Mobile: +91 97511 06000 sales@carlstahlcraftsman.com www.carlstahlcraftsman.com

